



NOTE:1.USB-A-SP MOLDING NO: A2H0508
 2.USB-A-SS INTER AND OUTER MOLDING NO: A2H0509
 3.CABLE MUST ACCORD USB STANDARD BUT NOT PRINT ANY WORD

PIN OUT	
P1	P2
1 ———	1 ———
2 ———	2 ———
3 ———	3 ———
4 ———	4 ———
SHELL	SHELL

7	TUBE	BLACK H.S.T OD:1.5*L8MM	1
6	OVERMOLD	PVC 45P IVORY	15
5	PERMOLD	PE	5
4	TINNED	OD:1.0	0.2
3	CONN	USB A TYPE FEMALE WHITE ALL THE SHELL	1
2	CONN	USB A TYPE MALE WHITE NICKEL-PLATED+SHELL	1
1	CABLE	UL2725 1P#28+2C#24+BARE COPPER AEB OD:4.5 TRANSPARENCE IVORY L:305MM	1/2

ワイエスソリューションズ株式会社

UNLESS OTHERWISE SPECIFIED
 TOLERANCE
 * . ± ; ** ± ; *** ± ; angles ± ;

DESCRIPTION: USB A TYPE M TO F MD NL=1FT	
CUSTOMER P/N:	A43
PRODUCT NO.:	280201
DWG NO.:	SHEET:1 of 1
REV: X/0	UNIT: mm
DATE:07.11.16	

NO.	TITLE	DESCRIPTION	Q'TY
△			
△			
△			
REV.	DESCRIPTION	DATE	APPROVED:

DRAWN:	
CHECKED:	
APPROVED:	

